

# TW-7700

## SINGLE FREQUENCY DIGITAL LINE TRACER



The state-of-the-art TW-7700 utilizes advanced digital signal processing for precision locating performance yet is extremely easy to use.

The lightweight receiver is simple to use. The display is a large and easy to read LCD that gives the user all the necessary information to do the job. A digital keypad allows the user to set the volume level, check the battery level, or activate an LCD backlight. Depth measurement is done at the push of a button.

The transmitter allows the user to locate in either a conductive or inductive mode. A meter and switch make transmitter set up simple and quick.

In the Fisher tradition, the TW-7700 is affordable, tough, and simple to use while providing maximum performance. A two year limited warranty comes standard with the unit.

### Features

- Advanced digital signal processing for accurate locating
- Instant target response
- Automatic gain control for maximum sensitivity
- Audio and visual left/right guidance
- Large easy to read LCD display
- Push button depth measurement
- Operates on standard batteries
- Hard or soft carrying case standard equipment
- Weather resistant design

since 1931

# FISHER<sup>®</sup> m-SCOPE

find it with

### FISHER RESEARCH LABORATORY

200 W. Willmott Rd., Los Banos, CA 93635-5501

T 209.826.3292 F 209.826.0416 website: [www.fisherlab.com](http://www.fisherlab.com) email: [info@fisherlab.com](mailto:info@fisherlab.com)

Fisher offers an extensive range of electronic detection instruments designed to meet the needs of the utility industry. From pipe & cable locators, valve & box locators, sound & leak detectors to water level indicators, find it... with Fisher.

# TW-7700 specifications



Specifications subject to change without notice.

## Receiver

- Depth Accuracy .....  $\pm 1$  inch per foot in nominal conditions
- Readout Units ..... Inches or cm (factory preset)
- Left/Right Guidance ..... Audio: continuous tone=Left, pulsed tone=Right. VCO (varying pitch) output for easy over target location. Visual: Left/Right/Over Target messages
- Signal Strength ..... Digital Numeric Readout (0-99%) & Bar Graph
- Sensitivity Adjust ..... Automatic
- LCD Backlight ..... Included
- Battery Test ..... Automatic Low Battery alert Push button readout
- Battery Type ..... Six "C" cells
- Battery Life ..... 80 Hours
- Weight ..... 5.4 lbs.
- Operating Temp .....  $-4^{\circ}$  to  $+140^{\circ}\text{F}$  ( $-20^{\circ}$  to  $+60^{\circ}\text{C}$ )



## Transmitter

- Output Frequency ..... 82kHz,
- Output Power (nominal) ..... .5Watts,
- Battery Test ..... Yes
- Battery Type ..... Two 6 Volt lantern batteries
- Battery Life ..... 80 Hours
- Weight ..... 5.0 lbs.

## Accessories

**Headphones** - Volume adjusts separately for each ear.

**Coupling Clamp** - Useful for in-service and electrical power line tracing when a metal-to-metal hookup is not possible

<b>2-Year Warranty</b>	Fisher warrants the TW-7700 to be free of defects in materials and workmanship when it is shipped from the factory. The terms of this warranty are fully explained in a warranty registration card that accompanies the instrument. Complete factory and field service facilities support the warranty. *Warranty may vary outside the U.S. See your distributor for details.
------------------------	---